

General lighting P 27



Image: General lighting P 27 Do Inno
(double-stack innovation train)
front view, with integrated loudspeaker



Image: Combination of luggage carrier flap P 27 Do Inno (above) and general lighting P 27 (below)

For the general lighting a 1,5 mm powder-coated steel sheet bar is used on which a loudspeaker facing board, a parabol mirror grate and dummy plates are mounted. The general lighting is available in different sizes and various combinations with the luggage carrier flap P 27. According to customer requests the light fitting can be equipped in different variations.

References

- Do Inno Baden Württemberg
- Do Inno Niedersachsen Bremen



State: September 2008
Technical subject to change without notice.

Technical parameters

General lighting P 27

Technical parameters

Design: powder-coated steel sheet bar with loudspeaker cover, parabol mirror grate and dummy plate

Other technical data

Dimensions: length/width/height 1335-934/102/65,5 mm
Fire protection: DIN 5510
Degree of protection: IP 20

Light bulbs (socket G13)

(Not included in the scope of delivery!)

Fluorescent lamp T8, 18 W

Fluorescent lamp T8, 36 W

Lamp operating device

Electronic ballast 24 V DC / 18 W

Electronic ballast 24 V DC / 36 W

Length	Light bulbs	Order no.
1282 mm	1 x 18 W	P 27 1800 - P 27 1809
1399 mm	1 x 18 W	P 27 1810 - P 27 1819